

DISMANTLING PIECES



Pipe lines are heavy and they are not flexible. They cannot be moved to install or uninstall a valve or similar equipment. To make the job easy, dismantling piece is used.

It is a type of product which consists of sliding flanged pipes, a flange (retainer ring), a rubber ring, studs and nuts. It is used for easy installation and un-installation of valves or similar equipments to pipe line or to each others. Face-to-face dimension of dismantling piece can be changed ($\pm$ 25 mm) to perform its duty.

The space between two flanges at the pipe line, where dismantling piece to be installed, should be the same with face-to-face dimension of dismantling piece mentioned in the catalogue. The shortest face-to-face is obtained by sliding two flanged pipes of dismantling piece on each others. The dimension is 25 mm shorter than catalogue value. This feature makes possible to install or un-install a valve or any other equipment or to fix flange gaskets.

One flange of dismantling piece is connected to the flange of pipe line. Then, other flange of dismantling piece is connected to other flange of pipe line by sliding flanged pipes on each others. Dismantling piece is fixed by tightening studs and nuts. Retainer ring in the middle, which presses on rubber ring, is also tightened till sealing performance of rubber ring is acceptable. Installation job is completed.

For un-installation job, these steps are followed from the end.



Product Code : DP-T

Full Stud Design Dismantling Piece



Product Code : DP-P

Partial Studs Design Dismantling Piece

DISMANTLING PIECE



Full Stud Design Dismantling Piece, Product Code, DP-T

Full stud design is the name for the type that all flange holes are fitted with studs. All flange connection holes are fitted with studs. It does not require additional bolts for connection. The retainer, which presses on rubber ring, is also tightened by nuts on these studs.

This design is preferred especially for PN 25 and greater pressure ratings to prevent misalignment of sliding flanged pipes. However, it is applicable for all pressure ratings upon request.

Maintenance,

No maintenance is needed for a dismantling piece installed in a pipe line. If it is uninstalled, we recommend checking rubber ring and changing if necessary.



Partial Studs Design Dismantling Piece, Product Code, DP - P

Partial stud design is the name for the type that all flange holes are not fitted with studs.

Same sizes of bolts are used for connection holes that do not have studs.

Retainer ring is tightened just enough for sealing performance of rubber ring.

Long studs are used for one of four holes but total quantity is not less than four pieces. Duty of long studs is to prevent misalignment of sliding flanged pipes.

This design is applicable for pressure ratings up to PN25.

This design is preferred for its advantages of easy installation and low cost.


Maintenance,

No maintenance is needed for a dismantling piece installed in a pipe line. If it is uninstalled, we recommend checking rubber ring and changing if necessary.

DISMANTLING PIECE - FULL STUD

Displacement, ± 25 mm


Maximum allowable working temperature for all types of our valves is 80 degrees Celcius.



DIMENSIONS

Inch	ANSI 125			ANSI 250			ANSI 250			ANSI 300		
	L	L1	Kg	L	L1	Kg	L	L1	Kg	L	L1	Kg
4	200	286	22	200	286	22	208	306	31	208	306	31
5	200	286	27	200	286	27	225	344	50	225	344	50
6	202	302	35	202	302	35	222	346	60	222	346	60
8	232	348	52	232	348	52	254	395	111	254	395	111
10	239	369	76	239	369	76	265	424	169	265	424	169
12	240	376	101	240	376	101	270	439	239	270	439	239
14	281	431	140	281	431	140	315	502	324	315	502	324
16	283	446	180	283	446	180	321	525	446	321	525	446
18	285	452	215	285	452	215	323	531	476	323	531	476
20	298	470	259	298	470	259	341	562	595	341	562	595
22	300	487	316	300	487	316	344	580	742	344	580	742
24	302	494	367	302	494	367	352	603	893	352	603	893
26	310	516	441	310	516	441	354	609	1.023	354	609	1.023
28	312	522	499	312	522	499	356	615	1.104	356	615	1.104
30	350	583	603	350	583	603	396	681	1.421	396	681	1.421
32	352	589	685	352	589	685	398	688	1.592	398	688	1.592
36	356	602	823	356	602	823	411	719	2.016	411	719	2.016
40	368	644	1.117	368	644	1.117	408	724	2.295	408	724	2.295
42	390	670	1.237	390	670	1.237						
44	391	675	1.326	391	675	1.326						
48	400	694	1.544	400	694	1.544						


DISMANTLING PIECE



PARTS

No	Item Name	Material	Description	EN Standard	Material No
1-4	Long and Short Body	GGG 40	Ductile Iron	EN-GJS-450-15	0.7040
		GGG 50		EN-GJS-500-7	0.7050
		St 37-2	Steel Construction	EN 10025	1.0037
2	Retainer Ring	St 37-2	Steel	EN 10025	1.0037
3	Ring	NBR, EPDM	Rubber	-	-
5	Flange of Pipe Line	-	-	-	-
6	Studs Nuts	Galvanized	Steel	-	-
		A 2 - A 4	Stainless Steel	-	-
Coating		WRAS approved fusion bonded epoxy. 300 microns dft as standard.			
Maximum allowable working temperature for all types of our valves is 80 degrees Celcius.					

FLANGE DIMENSIONS



Nominal Dia	Outside Dia	Raised Face		Flange Holes			Flange Thickness	Outside Dia	Raised Face		Flange Holes			Flange Thickness
		Dia	Height	Circle Dia.	Dia	Num ber			Dia	Height	Circle Dia.	Dia	Num ber	
DN	D	G	f	K	d	n	b	D	G	f	K	d	n	b
PN 10								PN 16						
100	220	158	3	180	19	8	19	220	158	3	180	19	8	19
125	250	188	3	210	19	8	19	250	188	3	210	19	8	19
150	285	212	3	240	23	8	19	285	212	3	240	23	8	19
200	340	268	3	295	23	8	20	340	268	3	295	23	12	20
250	395	320	3	350	23	12	22	405	320	3	355	28	12	22
300	445	370	4	400	23	12	25	460	378	4	410	28	12	25
350	505	430	4	460	23	16	25	520	438	4	470	28	16	27
400	565	482	4	515	28	16	25	580	490	4	525	31	16	28
450	615	532	4	565	28	20	26	640	550	4	585	31	20	30
500	670	585	4	620	28	20	27	715	610	4	650	34	20	32
600	780	685	5	725	31	20	30	840	725	5	770	37	20	36
700	895	800	5	840	31	24	33	910	795	5	840	37	24	40
800	1.015	905	5	950	34	24	35	1.025	900	5	950	41	24	43
900	1.115	1.005	5	1.050	34	28	38	1.125	1.000	5	1.050	41	28	47
1.000	1.230	1.110	5	1.160	37	28	40	1.255	1.115	5	1.170	44	28	50
1.200	1.455	1.330	5	1.380	41	32	45	1.485	1.330	5	1.390	50	32	57
1.400	1.675	1.535	5	1.590	44	36	46	1.685	1.530	5	1.590	50	36	59
1.500	1.785	1.640	5	1.700	44	36	48	1.820	1.640	5	1.710	57	36	63
1.600	1.915	1.760	5	1.820	50	40	49	1.930	1.750	5	1.820	57	40	65
1.800	2.115	1.950	5	2.020	50	44	52	2.130	1.950	5	2.020	57	44	69
2.000	2.325	2.150	5	2.230	50	48	55	2.345	2.150	5	2.230	62	48	73
2.200	2.550	2.370	5	2.440	57	52	59	2.555	2.360	5	2.440	62	52	80
PN 25								PN 40						
100	235	162	3	190	23	8	19	235	162	3	190	23	8	19
125	270	188	3	220	28	8	19	270	188	3	220	28	8	24
150	300	218	3	250	28	8	20	300	218	3	250	28	8	26
200	360	278	3	310	28	12	22	375	285	3	320	31	12	30
250	425	335	3	370	31	12	25	450	345	3	385	34	12	35
300	485	395	4	430	31	16	28	515	410	4	450	34	16	40
350	555	450	4	490	34	16	30	580	465	4	510	37	16	44
400	620	505	4	550	37	16	32	660	535	4	585	41	16	48
450	670	548	4	600	37	20	34	685	560	4	610	41	20	50
500	730	615	4	660	37	20	37	755	615	4	670	44	20	52
600	845	720	5	770	41	20	42	890	735	5	795	50	20	58
700	960	820	5	875	44	24	47	995	840	5	900	50	24	63
800	1.085	930	5	990	50	24	51	1.140	960	5	1.030	57	24	68
900	1.185	1.030	5	1.090	50	28	56	1.250	1.070	5	1.140	57	28	73
1.000	1.320	1.140	5	1.210	57	28	60	1.360	1.180	5	1.250	57	28	80
1.200	1.530	1.360	5	1.420	57	32	69	1.575	1.385	5	1.460	62	32	88
1.400	1.755	1.570	5	1.640	62	36	74	1.795	1.600	5	1.680	62	36	98
1.500	1.865	1.680	5	1.750	62	40	75	1.910	1.700	5	1.790	70	40	102
1.600	1.975	1.790	5	1.860	62	40	81	2.025	1.815	5	1.900	70	40	108
1.800	2.195	2.000	5	2.070	70	44	88							
2.000	2.425	2.230	5	2.300	70	48	95							